

● YOUR
● SMART
● ENERGY



STORION T50/T100

COMMERCIAL &
INDUSTRIAL SERIES

CAPACITY ►

34.4 kWh modular
expandable to 1032.2 kWh



UPS ability

Off-grid ability

Modular design

Easy installation and
low maintenance

24/7 Monitoring with
local interface



STORION T50/T100



Model		Storion-T50/T100	
System Specification			
Model	Storion-T50	Storion-T100	
Nominal AC Power	50 kW	100 kW	
Max. PV Input Power	100 kW	200 kW	
Capacity Range	34.4 kWh ~ 1032.2 kWh (90% DoD)		
Battery Chemistry	LFP (LiFePO4)		
Application Environment	Indoor (Rack) / Outdoor (Container)		
Warranty	3 Year Product Warranty, 10 Year Performance Warranty		

Inverter Technical Specification				
Max. PV Input Current	110 A	220 A	Phase	Three-Phase
PV Input Voltage Range	520 ~ 900 V		Nominal AC Current	72 A 144A
MPPT Number	1		Off-grid Voltage Range	360 ~ 440 V
Battery Voltage Range	250 ~ 520 V		Rated Frequency	50 / 60 Hz
Max. Charging/Discharging Current	150 A	300 A	Backup	UPS (With STS Module)
Max. Charging/Discharging Power	50 kW	100 kW	Dimension (W x D x H)	800 x 800 x 2160 mm
Rated Voltage	400 V		Weight	520 kg 750 kg
Grid Voltage Range	340 ~ 460 V		Grid Regulation	AS 4777.2/1.3
Power Factor Range	1 (lagging) ~ 1 (leading)		Safety	IEC 62109-1&-2

Battery Technical Specification		
Module Model	M48112-S	M38210-S
Module Weight	65 kg	62 kg
Module Dimension (W x D x H)	450 x 580 x 165 mm	332 x 570 x 223 mm
Max. Charging/Discharging Current	112 A (1C)	105 A (0.5C)
Module Capacity	5.7 kWh	8.1 kWh
Module Nominal Voltage	51.2 V	38.4 V
Cycle Life	≥ 6000	≥ 6000
Operating Temperature Range	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*

High Voltage Control Box Technical Specification		
BMU Model	HV900112 <small>(TOP BMU required with more than one cluster)</small>	HV900105 <small>(TOP BMU required with more than one cluster)</small>
DC Voltage Range	200 ~ 900 V	
Nominal Output Current	112 A	105 A
Battery Modules Connection	6 ~ 9 M48112-S in series in one cluster	8 ~ 12 M38210-S in series in one cluster
Clusters Connection	Max. 20 clusters in parallel	

* When the temperature is below 0 °C or above 40 °C, the performance will be limited.



Headquarter: Alpha ESS Co., Ltd.
 ☎ +86 (0) 513 8060 6891
 ✉ info@alpha-ess.com
 🌐 www.alpha-ess.com
 📍 Jihua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.
 ☎ +86 (0) 512 6828 7609
 ✉ info@alpha-ess.com
 🌐 www.alpha-ess.com
 📍 Level 15, SIP 158 Wangdun Road SIP Suzhou, 215028

Australia: Alpha ESS Australia Pty. Ltd.
 ☎ +61 (0) 402 500 520 (Sales)
 +61 1300 968 933 (Technical Support)
 ✉ australia@alpha-ess.com
 🌐 www.alpha-ess.com.au
 📍 Suite 1, Level 1, 530 Botany Road, Alexandria, NSW, 2015

Germany: Alpha ESS Europe GmbH
 ☎ +49 (0) 6103 / 459 160-1
 ✉ europe@alpha-ess.de
 🌐 www.alpha-ess.de
 📍 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Italy: Alpha ESS Italy S.r.l.
 ☎ +39 (0) 599 239 50
 ✉ info@alpha-ess.it
 🌐 www.alpha-ess.it
 📍 Via Loda, 17-41013 Castelfranco Emilia (MO)

Korea: Alpha ESS Korea Co., Ltd.
 ☎ +82 64 721 2004
 ✉ korea@alpha-ess.com
 📍 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

UK: Alpha ESS UK Ltd.
 ✉ uk@alpha-ess.com
 📍 Drake House, Long Street, Dursley, gl11 4hh